# PREMIUM INTERNATIONAL EVENTS

Elevate Every Sound, Amplify Every Moment

Welcome to our Audio Equipment List , Find more info visit our website www.PremiumEvents-SA.com



Premium Audio Rental is a leading audio rental company operating in Saudi Arabia and Dubai, specializing in high-quality sound solutions. We provide comprehensive technical support for major events, ensuring exceptional audio performance with cutting-edge equipment and expert services.



# 24X L-Acoustics K1 Line Array

The industry benchmark

3-way active, dual 15"

Max SPL 149 dB

Bandwidth 35 Hz- 20 KHz

Transduces LF: 2 x 15"


MF: 4 x 6.5"

HF:3 x 3"

Weight 106 kg / 234 lb

Directivity H: 90°

V: 5°





# 16X K1-SB | Long Throw Professional Audio Subwoofer

Flyable high power subwoofer Bass-reflex, dual 15"

**L-VENTS** 

Max SPL 145 dB

Bandwidth 30 Hz

Transducers LF:2x

15"

Weight 83 kg /183 lb





# **48 L-Acoustics K2 Line Array**



## K2

Lightweight heavyweight

3-way active, dual 12"



VARIABLE CURVATURE LINE SOURCE







Max SPL	147 dB
Bandwidth	35 Hz- 20 KHz
Transducers	LF: 2 x 12" MF: 4 x 6.5" HF: 2 x 3"
Weight	56 kg / 123 lb
Directivity	H: 70° / 90° / 110° V: 10°




# 48 L-Acoustics Kara Line Array

The KARA modular line source élément has an operating frequency bandwidth from 55 Hz to 20 kHz. This response can be lowered down to 32 Hz with the addition of the SB18 low-frequency extension.

KARA features a 2-way, biamplified design and is equipped with 2 x 8" neodymium LF speakers in a Bass-reflex tuned enclosure. The HF section features a 3" neodymium diaphragme driver coupled to a DOSC® waveguide.

The K-shaped coplanar transducer configuration generates a symmetric horizontal coverage of 110° without secondary lobes over the entire frequency range.

The combination of coplanar symmetry and DOSC® waveguide allows the system to



fulfill the 5 WST® criteria. Any KARA line source can be curved up to a maximum of 10° for each element without breaking the inter-element acoustic coupling



### 48 L-Acoustics Subwoofers SB28

High-Power Subwoofer
25Hz LF limit, exceptional power handling capability

Progressive vent for increased peak SPL, and minimal turbulence noise

LA8 amplified controller drive and protection

DSP presets for cardioid mode (symmetrical and asymmetrical)



#### 12 L-Acoustics Subwoofers SB18

#### High Power compact subwoofer

32 Hz LF limit, high power handling, low distortion and thermal compression

Progressive vent for increased peak SPL,

and minimal turbulence noise

DSP presets for cardioid mode

(Symmetrical and asymmetrical)

Pole mount for X series, ARCS® Wide/Focus and KIVA II

Compatible rigging: SB18(i)/Kara®(i)





#### • LA-RAK - L Acoustics

Modular touring rack designed for all L-ACOUSTICS systems: -

- Hosts 3 x LA8 for maximum drive flexibility and power
- Analog Signal, Network and Power distribution panels
- Engineered 9U frame allows flying and rigging
- Compatible with legacy cabling standards
- Universal platform to ease L-ACOUSTICS Rental Network cross rental
- AES/EBU Standard on LA8 and LA-RAK



#### **LA4X - L-Acoustics**

- Output Power 4 x 1000 W at 4 and 8 ohms
- Power supply Universal SMPS with PFC
- Inputs AVB, AES, Analog





# **L-Acoustics Syva**

Syva combines the advantages of the direct effect of long line speakers with the coupling of DOSC waveguides in the treble range. As a result, it achieves a perfectly controlled, narrow vertical radiation down to 300 Hz. Syva focuses the energy on the rear area of the audience and at the same time offers an even distribution of sound downwards into the close range. Range and sound pressure are consistent from the near to the far range. The combination of a long range of up to 35 meters and the extremely wide sound distribution ensures exceptionally good coverage.





## L-Acoustics Focus & A15 Wide

A15 Focus & A15 Wide Performance and simplicity 2-way passive, 15"

Max SPL 144 dB

Bandwidth 41 Hz- 20 KHz


Transducers LF: 1 x 15"

HF: 1 x 3"

Weight 35 kg / 77 lb

Directivity H: 70° / 90° / 110°

V: 10°







# **L-Acoustics Stage Monitors**

#### 16 L-Acoustics 115XT HIQ

Usable bandwidth (-10dB)	50 Hz - 20 kHz ([HIQ_FR] preset)
Nominal directivity (-6dB)	50° Axi-symmetric
Maximum SPL <sup>1</sup>	139.5 dB ([HiQ_MO] preset) 136.5 dB ([HiQ_Fi] preset)
RMS handling capacity	LF: 450 W HF: 125 W ([HiQ_FI] preset)
Components	LF: 1 x 15" neodymlum transducer HF: 1 x 3" diaphragm compression driver Nominal impedance: 2 x 8 ohms
Physical data	H x W x D: 365 x 580 x 440 mm - 14.4 x 22.8 x 17.3 in Wedge angle: 30° or 60° from vertical Weight (net): 28.5 kg - 62.8 lbs.  Connectors: 2 x 4-point Speakon® Material: 18, 24 and 30 mm Baltic birch plywood Finish: Grey-brown RAL 8019® Front: polyester-powder coated steel grill, acoustically transparent Airnet® cloth Rigging: Integrated handles and pole mount socket, optional ETR15 bracket and XTLIFTBAR accessory



#### 8 L-Acoustics 12XT

Usable bandwidth (-10dB)	55 Hz - 20 kHz ([I2XTA_FR] preset)
Nominal directivity (-6dB)	90° Axi-symmetric
Maximum SPL <sup>1</sup>	133 dB ([12XTA_FI] preset)
RMS handling capacity	12XT Passive: 380 W ([  12XTP_FI] preset)   12XT Active: LF: 290 W - HF:   35 W ([12XTA_FI] preset)
Components	LF: 1 x 12" weather-resistant transducer HF: 1 x 3" diaphragm compression driver Nominal Impedance: 8 ohms (passive), 2 x 8 ohms (active)
Physical data	H x W x D: 540 x 410 x 389 mm - 21.3 x 16.1 x 15.3 in. Wedge angle: 30° or 60° from vertical Weight (net): 29 kg - 63.9 lb. Connectors: 2 x 4-point Speakon® Material: 18, 24 and 30 mm Baltic birch plywood Finish: Grey-brown RAL 8019® Front: polyester-powder coated steel grill, acoustically transparent Airnet® cloth Rigging: integrated handles and pole mount socket, Omnimount® compatibility, optional ETR12-2 bracket and XTLIFTBAR accessory

Peak level measured at 1m under free field conditions using 10 dB crest factor pink noise with specified preset and corresponding EQ settings.



<sup>1</sup> Peak level measured at 1m under half-space (MO) or free field (FI) conditions using 10 dB crest factor pink noise with specified preset and corresponding EQ settings.



# L-Acoustics X15 HiQ

#### Reference stage monitor

- Power (SPL) in beamwidth and acoustic isolation
- High immunity to feedback
- Narrow ellipsoid directivity of 40° x 60°
- Low profile and weight for integration and handling
- Rugged build
- Active design with low latency preset



### L-Acoustics X12 HIQ

#### Multipurpose enclosure

- Ellipsoid directivity of 90° x 60° for FOH
- Shape, size and RAL color for easy integration
- Low weight and ergonomics for handling
- Complete range of rigging accessories
- Passive design, optimized amplified controller quantum





### **48X AIPHA3 Column Speakers**

1,000W Powered Modular Column Loudspeaker with 12" Subwoofer, 16 x 2.75" MF Drivers, 1 x 1" HF Compression Driver, Klark Teknik Spatial Sound Technology, Digital Mixer, Bluetooth Audio Streaming, and iPhone/iPad Remote Control (each)

- Compact modular design for maximum portability and easy setup
- Spatial Sound technology for creation of 3D acoustic environments
- Comprehensive DSP presets for typical user applications
- Custom-engineered drivers for outstanding sound dispersion
- 12" low-frequency driver with high excursion for lowdistortion sub bass response
- 16 x 2.75" neodymium drivers with edge-wound aluminum voice coils for extended high-frequency reproduction
- Class D amplifier provides you with massive power and efficiency
- Built-in digital mixer for simple, complete control
- Intuitive single-knob user interface with LCD display for ease of navigation



- Convenient remote operation with your iPhone or iPad
- Bluetooth capabilities allow for easy audio streaming
- Precision-lock, aluminum array system eliminates speaker stands and cables
- Road-worthy plastic enclosure with hardwearing semi-matte black finish
- Integrated protective perforated steel mesh grilles

### 200 RCF ART 715-A MK4

- ACTIVE TWO-WAY SPEAKER
- Two Channel Amplifier of 1400 WATT
- 130 dB Max SPL
- 1" Compression Driver, 1.75" v.c.

#### **FEATURES**

- 130 dB Max SPL
- Two Channel Amplifier of 1400 WATT
- Innovative DSP Processing
- 1" Compression Driver, 1.75" v.c.
- 15" Woofer
- 90°x60°, wide dispersion constant directivity horn
- FiRPHASE Technology

#### 48X RCF ART 715 H-BR









# **Mixers**

### Yamaha CL5 Tour Pack

Input 72 Mono + 8 Stereo Input Mixing Channels,

Output 24 Mix Buses, 8 Matrices and Dante Input/ Output.



2 X Rio3224-D I/O Rack Rio3224-D provides 32 ins, 16 outs, and four AES/EBU outputs.

1 X Rio1608-D I/O Rack The 3U size Rio1608-D has 16 ins and 8 outs.





#### Yamaha QL5 Digital Mixer

Channels 64 mono, 8 stereo mixing channels Inputs - Mic Preamps 32 x XLR Phantom Power 32 channels Inputs - Digital 2 x EtherCon Cat5 (Dante Primary, Secondary)
Outputs - Digital 1 x XLR (AES/EBU), 2 x EtherCon (Dante Primary, Secondary)
Outputs - Main 16 x XLR (Omni)
MIDI I/O In, Out
Data I/
Channel InsertsYes
Busses/Groups 16 x Bus

Two-track recording and multitrack options 64 Channels



Cat5

#### Sound craft MH2 48 Channel Console

MH2 48 Channel Console - 48 Mono, 4 Stereo, 10 Aux, 8 Groups, 4 Matrix

48 channel frame, 4 stereo channels, 10 aux sends, 8 groups, 4 matrix outputs, 8 VCA groups
Premium MH series mic preamps with 50dB of headroom and a - 20dB pad on every channel
4-band fully sweepable "British" EQ with highs, high-mids, low-mids, and lows Internal and external redundant power supply options





# **Digico Quantum 338 Digital Mixing Console**



128-Input Digital Mixing Console With 38 Faders, 64 Buses, LR/LCR/LCRS/5.1 Master Bus, 24-In/24-Out Processing Matrix, 286 Dynamic Equalizers, And 48khz/96khz Sampling Rate

#### 2X DiGiCo SD-Rack Input/Output Rack Equpied with Two SD rack 32 BIT.

- 14 card module slots 56 inputs and 56 outputs
- Fully compatible with our industry leading 32bit SD cards
- 192kHz high resolution ready
- HMA Optics
- Redundant power supplies





Yamaha DM7 120-channel Digital Mixer

Premium Audio rental invested in two desks full size

To supply maximum number of inputs for our client.

120-channel, Dual-bay Digital Mixer with 32 Mic Preamps, 28 Motorized Faders, 2 x 12" Touchscreens, 1 x 7" Touchscreen, 18-in/18-out Audio Interface, 144-in/144-out Dante Interface, and Al Assist.




## Yamaha CSD-R7 Digital Mixing Console

The CSD-R7 Digital Mixing Console is the core component of any RIVAGE PM7 system, with 96 kHz processing, 120 monaural inputs, and a versatile complement of mixing busses (60 MIX, 24 MATRIX, and 2 STEREO). The console has three 12-faders bays for flexible setup and configuration, and dual power supply units are built in for enhanced reliability.





# Yamaha RIVAGE PM5 Digital Mixing Console



The CS-R5 control surface is the core component of RIVAGE PM5 system, with 96 kHz processing. The console has three touch screen and 12-faders bays for flexible setup and configuration. Touch panels are brought closer to the user, making them easier to reach. The weight is 92.6lbs (42kg) which is incredibly light.

- Display: 15" touch panel x 3
- Faders: 38 (12+12+12+2)
- Selected Channel section: Dynamics, GAIN, HPF, EQ, PAN, Function Knob
- Custom Fader banks: 6 x 5 on each bay
- User Defined keys: 12 x 4 banks
- Send/User Defined knobs: 3(4 x 4 banks can be assigned)
- Touch and Turn knobs: 3
- Analog I/O: 8 in / 8 out
- Slot: 2 MY slots
- AES/EBU: 4 in / 4 out (with SRC)
- Ports: GPI (8 in / 8 out), MIDI In/Out, 5 USB (1 for 2-track recording)
- Power supply: Dual redundant power supply built-in
- Power consumption: 300W



## **Axient® Digital Wireless Microphone System**





# Microphones & Wireless Systems & In-Ear Monitoring

#### 32 Channels Shure UR4D Combo Package

- G1 band (470-530 MHz)
- 2,400 selectable frequencies across 60 MHz bandwidth
- Track Tuning filtering technology
- Up to 40 preset compatible systems per band
- Up to 108 systems with multiple bands
- Networked automatic frequency selection



# Shure ULXD4Q Combo Package

ULXD4Q Quad Channel Digital Wireless Receiver



# **UA844+SWB Antenna Distribution System**

Wideband UHF (470-952 MHz) Four-Way Active Antenna Splitter and Power Distribution System, external power supply. For QLX-D™, ULX®, ULX-D®, SLX®, and BLX® (BLX4R only) receivers.



# **Shure UA845-SWB Active Antenna Splitter**

Five-Way Active Antenna Splitter and Power Distribution System for U4S, UR4S, U4D, and UR4D receivers; Five-Way Active Antenna Splitter for ULXD4, UXLD4D, ULXD4Q receivers.



# Shure UA874 Active Directional Antenna

Active directional UHF antenna with integrated amplifier for improved wireless signal reception.



MX412 & MX418 Gooseneck Microphones





# Conferencing & Meeting Microphone Applications

Premium Audio Rental Owen in Stock 150 X MXC605 Conf Unit Portable.

Premium Audio Rental was appointed by Shure Conferencing Network (SCN) rental partner to support this event with simultaneous interpretation and discussion systems.



Premium Audio Rental powered four Meetings with the Shure conferencing network and deployed L- Acoustics and a complete Shure Audio network solution powered with Shure Conferencing Network DDS 5900 Discussion System, by installation with up to 60 microphone units specific for chairman and delegates Microphones to meet all Audio require .



Shure PSM 900 Wireless Personal Monitor System (G6: 470.125 to 505.825 MHz) Shure P9RA+ Wireless Bodypack Receiver (G6: 470 to 506 MHz)



# Sennheiser E604 Dynamic Cardioid Instrument



SHURE ULXD8
WIRELESS TABLE
Gooseneck Base
Transmitter



Sennheiser ME36 MZH Shotgun Microphone Capsule (Black)



### DPA Microphones d fine 4088 Omnidirectionnel Headset



**Shure SM35 Performance Headset** 





# Neumann KM184 Stereo Set



### **AKG C214 Stereo Set**



Sennheiser E 906





# **Shure BETA 91A - Kick Drum Microphone**



# Shure SM81 (Pair)



Audix DP7 7-piece Drums Mic Package





# **Shure WL185 Lavaliere Condenser Microphone**



**Shure MIC 57 & 58** 



**K&M** microphone & Music Note Stand






# 50 X Audio-Technica ATH-M40x



# 16 Channel Digital Personal Mixer



# **Behringer Powerplay PM1**





#### 50X Sennheiser HD-25 Plus



#### Sennheiser SR 2050 IEM

- 1 Double transmitter IEM (Double IEM base) SR2050 IEM Cw
- 2 antennas BNC
- 2 x Bodypack EK2000 Cw freq.



#### 4 KIT DPA Microphone

#### Set consists of:

10x Core 4099 instrument microphones

10x Microdot adapters

10x Miniature microphone cables

8x Clips for violin

3x Clips for cello

2x Clips for piano


4x Clips for guitar

2x Clips for saxophone / trumpet

2x Universal clips

2x Clips for bass

2x Clips for drums





#### Earthworks Audio DM6

Condenser Kick Drum Mic with 20Hz-20kHz Frequency Response, Supercardioid Polar Pattern, and 150dB Max SPL



# Earthworks Audio DK7 FullKit SystemIncludes:

- 4 DM20 small-diaphragm cardioid condenser mics (for toms and snare)
- 2 SR25 small-diaphragm cardioid condenser mics (for overheads
- 1 SR20LS small-diaphragm cardioid condenser mic (for bass drum)
- 4 RM1 RimMount for DM20
- 4 PW1 foam windscreens for DM20
- 3 MC1 microphone clips for SR25/SR20LS
- 3 SRW3 foam windscreens for SR25/SR20LS





# Shure PSM 1000 Shure P10TR+425CL Wireless Personal Monitor System - G10 Band - 470-542MHz





# **Power Distribution Box**

Entrance: 3P + N + PE Power Lock Main 400A MCCB 3P

#### Exit:

- 2x CEE 125A 400V 5P
- 2x MCB 125A C 3P
- 2x CEE 63A 400V 5P
- 2x MCB 63A C 3P
- 9x CEE 32A 400V 5P
- 9x RCBO 32A C 30mA 4P
- 6x CEE 16A 230V 3P
- 6x MCB 16A C 1P



Entrance: 3P + N + PE Power Lock Main fuse 125A MCCB 3P

125 Amp power distributor Input: CEE 125A 400V 5P

#### Output:

- 2x CEE 63A 400V 5P 2x MCB 63A C 3P
- 2x CEE 32A 400V 5P 2x MCB 32A C 3P
- 1x RCD 63A 30mA 4P





### Pioneer CDJ- 900 player & DJM-700 Mixer







#### Pioneer 2X CDJ-2000NXS2 + DJM-2000NXS2





# Pioneer SET 2X CDJ-3000 + DJM-A9





2

# **BACKLINE RENTAL Catalogue**



#### Set configuration includes:

100% Maple wood

22" x 18" Bass drum

10" x 08" Tom Tom with 1.5 mm steel counter hoops

12" x 09" Tom Tom with 1.5 mm steel counter hoops

16" x 14" Floor Tom with 2.0 mm steel counter hoops

14" x 5.5" Snare Drum with 2.5 mm steel counter hoops



## **DW PDP CM7 Natural Lacquer**



#### **Drum Shell Set**

- Tom toms with 1.5 mm steel hoops
- Floor toms with 2.0 mm steel hoops
- Snare drum with 2.5 mm steel hoops
- Color Natural Lacquer

#### **Set configuration:**

- 22" x 18" Bass drum
- 08" x 07" Tom tom
- 10" x 08" Tom tom
- 12" x 09" Tom tom
- 14" x 12" Floor tom
- 16" x 14" Floor tom
- 14" x 5.5" Snare drum



Evans UV2 10" + 12" + 16" UV2 Coated drumheads Coated Tom Pack 10/12/16



Evans S14H30 14" Snare Resonant Head





## **DW 9000 Pedal**



# Ahead SPG-R3 Spinal Gl. Drum Throne





## Zildjian K Custom Worship Pack Set:-

#### Cymbal Set:

- 14" K Custom Dark Hi-Hat
- 16" K Custom Fast Crash
- 18" K Custom Fast Crash
- 20" K Custom Medium Ride



# Conga Set Aspire series LP LPA647-SW

- Material Walnut
- Color Brown
- Conga Sizes 11", 12"





# LPA601-SW Aspire Walnut Bongos

- Color Brown
- Size of the smallest bongo 6,75"



# LP 257-KP Timbales Karl Perazzo

#### Timbale Set

- Karl Perazzo Series
- Sizes: 14" and 15"
- Material: Steel drum shell
- LP drum head
- the largest bongo





## **Roland TD-30KV Electronic Drum Set - 6-piece**

#### Kit includes:

TD-30 Sound Module KD-140-BC V-Kick PD-128S-BC V-Pad (Snare) 2 PD-108-BC V-Pads (Tom 1 & 2) 2 PD-128-BC V-Pads (Tom 3 & 4) VH-13-MG V-Hi-Hat 2 CY-14C-MG V Crash Cymbals CY-15R-MG V Ride Cymbal Chrome Rack All Drum Pad and Cymbal Cables







## **LP Giovanni Palladium Wood Congas**

- 1 3/4" LP Giovanni Palladium Conga
- 12 1/2" LP Giovanni Palladium Tumbadora
- 14" LP Giovanni Palladium Super Tumbadora
- LP 793X Galaxy Giovanni Bongo Set







#### Markbass MB58R 104 Pure Box 8

Cabinet for Electric Bass

Equipped with: 4x 10" neodymium speaker and

1" hi-fi driver

Power rating: 800 W @ 8 Ohm

Frequency response: 35 Hz – 20,000 Hz

Crossover frequency: 3500 Hz Max. sound pressure level: 103 dB

Housing biodegradable



# Markbass Little Mark Tube 800 Bass Head

Tube preamp
800 Watt at 4 Ohm
500 Watt at 8 Ohm
Mix Controls Tube/Solid State
Pre/Post switch
Controls for Volume, Bass, Low and High mid
Treble, master volume
Variable Pre Shape Filter
Vintage Speaker Emulator
Line Out, Effect Send and Return, LINE OUT: Balanced XLR, Tuner Out
Ultra light and compact, Weight approx. 2.9 kg



# Ampeg SVT-610 HLF

#### **Bass Speaker**

- 6 x 10" Speaker + horn
- Rated power: 600 W at 4 Ohms
- Impedance 4 Ohm
- Crossover frequency: 5000 Hz
- Frequency response: 42 -18000 hz
- SPL: 125 dB maximum SPL



# Ampeg SVT-7Pro 1000-watt Tube Preamp Bass Head

- Number of Channels: 1
- Total Power: 1000W, 4 ohms/600W, 8 ohms/Class-D Power Amp
- EQ: 3-band (5-position Midrange), Ultra Lo/Hi Boosts
- Preamp Tubes: 12AX7





# Fender '65 Twin Reverb 85-watt 2x12 Tube Combo Amp

#### **Tech Specs**

• Type: Tube

Number of Channels: 2

Total Power: 85W

• Speaker Size: 2 x 12"

 Preamp Tubes: 4 x 12AX7, 2 x 12AT7

Power Tubes: 4 x 6L6

Reverb: YesEQ:3-band

• Inputs: 2 x 1/4" (normal), 2 x 1/4"

(vibrato)

• Outputs: 2 x 1/4" (speaker)



#### 2X Marshall JVM410H

Guitar amplifier head Power: 100 W

4 channels with all-tube technology - no semiconductor in signal path

Preamp tubes: 5 x ECC 83 Power amp tubes: 4 x EL34

Individual 3-band EQ as well as gain and volume for each channel





#### 2X Marshall 1960 A Bundle

- Power rating: 300 Watt
- Equipped with: 4 x 12" Celestion G12T-75
- Ohm Angled design
- Adjustable impedance: Mono 4/16 Ohm, stereo
- 2 x 8 Ohm



#### JC-120 Jazz Chorus Guitar Amplifier

Guitars Guitar Amps Guitar Combo

Amps Roland Jazz Chorus

Roland JC-120 Jazz Chorus 2 x 12-inch 120-watt

Stereo Combo Amp

120-watt, 2-channel 2x12" Guitar Combo Amplifier

with Reverb and Vibrato - Black





#### Markbass MB58R 151 Pure Box

Cabinet for Electric Bass

Equipped with: 1x 15" neodymium speaker and 1" hi-fi

driver

Power rating: 400 W @ 8 Ohm Frequency range: 40 - 20.000 Hz Crossover frequency: 3.5 kHz Sound pressure level: 100 dB SPL

# Adams Universal Timpani 26"+29"KH FS

#### Adams 29" 2PAUFKH29D FS German

- Hammered Universal Copper Pedal Kettle Drum
- Size: 29"
- Parabolic drum shell
- Fixed tuning pedal
- Tuning gauge
- Fine tuner
- 6 Tension rods
- Three supporting legs one with a braked caster wheel
- Tuning key

# Adams 26" 2PAUFKH26D FS German Hammered Universal Copper Pedal Kettle Drum

- Size: 26"
- Parabolic drum shell
- Fixed tuning pedal
- Tuning gauge
- Fine tuner
- 6 Tension rods
- Three supporting legs one with a braked caster wheelTuning key







## Salvi Ana Deluxe Mahogany

40-String Lever Harp
Top: Fiemme Valley red
spruce
40 Strings
Gold coloured machine heads
Range from high to low: 1st
octave E 1 to 6th octave A 6
Lever harp string tension

Height: 162 cm Width: 80 cm





#### **Adams MSGA43 70th Solist Marimba**

#### Solist Marimba

Thomann 70th Anniversary Model 4 1/3 Octaves from A2 - C7 Apex frame Sound bars made from granadillo, 58 - 40 mm

A = 442 Hz Length: 185 cm

Width at the bottom end: 90 cm Width at the top end: 40 cm

Height adjustable from 85 - 105 cover

Width: 38 cm Weight: 20 kg





# Gewa Europe RockabillyBass¾





## Gewa Basic Line Solid Bass 4/4

Full Massive Double Bass
Size: 4/4
Violin shape
Solid spruce top
Solid maple back
Inlaid purfling
Rubner tuners in Tyrolean brass
Ebony fingerboard
Reddish brown paint





## **Guitars**

Fender made in japan Traditional 60s Jazz Bass All Black.



Fender Electric Guitars Stratocaster AFFINITY SERIES™ STRATOCASTER® FMT HSS)

https://www.fender.com/en-US/squier-electric-guitars/stratocaster/affinity-series-stratocaster-fmt-hss/0378152547.html





## Les Paul Classic Deep Purple

https://www.gibson.com/en-US/p/Electric-Guitar/USAI9Q269/Deep-Purple



#### Fender Paramount Series Acoustic Guitar

https://www.fender.com/en-US/acoustic-guitars/dreadnought/pd-220e-dreadnought/0970310337.html





## **Keyboards**

### Yamaha MOTIF XF8 88-Key Synthesizer Workstation



- 88 keys, Balanced Hammer Effect Keyboard (Initial Touch/Aftertouch)
- 128 note polyphony
- The 741MB of internal wave ROM includes incredibly realistic pianos and acoustic instruments, vintage synths and the hip-hop sounds all of today's top producers are using.
- A sophisticated 8-element synth architecture with XSpanded articulation and 18 different filter types let you shape your sound anyway you want and the 8 front panel knobs and sliders make it easy to do even in real time.
- An additional 128 Voices and 8 drum kits, for a total of 1,353 highquality Voices



### **KORG KRONOS2 61 key**



KORG KRONOS2 61 key Keys Music Workstation Synthesizer

- With 61 lightly-weighted keys
- Sound engine: 9 Synthesis engines SGX-2, EP-1, HD-1, AL-1, CX-3, STR-1, MOD-7, MS-20EX and PolysixEX
- Polyphony: Up to max. 200 voices (depending on synthesis engine)
- Sampling: Open Sampling System (resampling, In-Track sampling)
- Master keyboard functions: Keyboard and velocity splits
- Layers and crossfades of up to 16 programs and/or external MIDI devices
- Advanced Vector Synthesis



### KORG Pa1000 61-Key Professional



#### **Tech Specs**

- Number of Keys: 61
- Type of Keys: Semi-weighted, velocity sensitive, aftertouch
- Other Controllers: Assignable Joystick
- Polyphony: 128 Notes
- Presets: Over 430 factory styles, 1,750 factory sounds (multilayer stereo piano, GM/XG sounds, drum kits)
- Effects Types: TC Helicon Voice processor, 148 song/sound effects, 45 guitar effects,
- Memory: 600MB PCM available (300MB compressed)
- Storage: MicroSD card slot, USB
- Formats: Korg, WAV, AIFF, Sound Font
- Sequencer: 16 track, SMF native format



### Nord Stage 3 HP76 76-key Stage Piano



#### **Product Features:**

- 73-Note, Semi-Weighted Waterfall Keybed
- Piano, Organ, and Synthesizer Sounds
- Clavinet and Harpsichord
- Sample Playback Capabilities
- Built-In Effects Section
- Syncronizable LFO and Arpeggiator
- Seamless Transitions
- Song Mode



## Yamaha Yamaha CLP 765 GP

Yamaha Clavinova CLP-765GP Digital Piano Overview - YouTube





#### **Roland SPD-SX Sampling Pad SE**

- Number of trigger pads 9
- Sampling function
- Number of Trigger inputs 2



### Yamaha Montage-8 88 Key

#### **Workstation Keyboard**



- Yamaha Montage 8 88-key Synthesizer Features:
- Aftertouch-enabled, 88-note Balanced Hammer Action keybed
- Polyphony is AWM2: 128 (max.; stereo/mono waveforms) FM-X: 128 (max.)



## **Roland Fantom 8**



## Synthesizer Workstation

- 88 PHA-50 hammer-action keyboard (wood/plastic composite structure), velocity sensitive and with aftertouch
- ZEN Core sound engine with 256 voices
- V-Piano and Supernatural sound engine
- More than 3500 preset sounds and over 90 drum kits





## KORG KRONOS 2-88 LS Keyboard Workstation

ey Features



- 88 Keys with LS Semi-Weighted Keyboard
- Velocity Sensitive
- 9 Sound Engines
- 16 Simultaneous Effects
- 16-Part Combinations and More
- Light-Touch Keyboard
- OS v3.1 with Quick Layer/Split Functions
- Lighter Weight and More Portable

The **KRONOS 88 LS Music Workstation** from **KORG** is a full-sized keyboard that has been designed with a light-touch keyboard for effortless playability. It can be used in several environments by musicians, sound designers, and engineers for live stage, theater, recording studio, and rehearsal applications.



## Yamaha Rydeen Standard Hot Red



### Complete drum set

- Rydeen Series
- Standard configuration
- Model: RDP2F5CY-RD
- 22" x 16" bass drum (drilled)
- 10" x 7" tom tom
- 12" x 8" tom tom
- 16" x 15" floor tom
- 14" x 5.5" Snare Drum
- . Incl. the Paiste 101 cymbal set:
- 14" hi-hat
- 16" crash
- 20" ride



## Ludwig LU5514C 14"x5,5" Univers Brass



Meinl Cymbals 16" Trash China with Holes – HCS Traditional Finish Bronze for Drum Set, Made in Germany, (HCSB16TRCH)



Meinl 12" China Cymbal – HCS Traditional Finish Brass for Drum Set, Made In Germany,



Meinl 10" China Cymbal – HCS Traditional Finish Brass for Drum Set, Made In Germany,





#### Zultan 16" Rock Beat Crash



### Cymbal set comprises:

14" HHX Evolution Hi-Hat 16" HHX Evolution Crash 18" HHX Evolution Crash 21" HHX Evolution Ride



